

片式压敏电阻器—SDV 系列

Chip Varistor for ESD – SDV Series



工作温度

Operating Temp

- 55°C~+125°C

特征

Features

- SMD 结构适合高密度安装
- 优异的限压比, 响应时间短 (<0.5ns)
- 良好的焊接性能 (镍、锡电镀)
- SMD type suitable for high density mounting
- Excellent clamping ratio and quick response time (<0.5ns)
- Excellent solderability (Ni, Sn plating)

用途

Applications

- IC 和晶体管的过电压保护
- USB、MIPI 等接口 ESD 防护
- MOSFET 保护
- 手机、TV 等便携式设备保护
- Transient voltage protection for IC and transistor
- ESD protection such as USB2.0, MIPI etc.
- MOSFET protection
- Portable equipment protection, such as mobile phone, TV, etc.

产品型号


Product Identification



1	2	3																						
<table border="1"> <tr> <th colspan="2">分类 Type</th> </tr> <tr> <td>SDV</td> <td>片式压敏电阻器 Chip Varistor for ESD</td> </tr> </table>	分类 Type		SDV	片式压敏电阻器 Chip Varistor for ESD	<table border="1"> <tr> <th colspan="2">外形尺寸 (L×W) (mm) External Dimensions (L×W) (mm)</th> </tr> <tr> <td>1005 [0402]</td> <td>1.0×0.5</td> </tr> <tr> <td>1608 [0603]</td> <td>1.6×0.8</td> </tr> <tr> <td>2012 [0805]</td> <td>2.0×1.25</td> </tr> </table>	外形尺寸 (L×W) (mm) External Dimensions (L×W) (mm)		1005 [0402]	1.0×0.5	1608 [0603]	1.6×0.8	2012 [0805]	2.0×1.25	<table border="1"> <tr> <th colspan="2">特征代号 Feature Code</th> </tr> <tr> <td>A</td> <td>For General Use</td> </tr> <tr> <td>E</td> <td>For ESD</td> </tr> <tr> <td>H</td> <td>For High Speed</td> </tr> <tr> <td>S</td> <td>For Special Request</td> </tr> </table>	特征代号 Feature Code		A	For General Use	E	For ESD	H	For High Speed	S	For Special Request
分类 Type																								
SDV	片式压敏电阻器 Chip Varistor for ESD																							
外形尺寸 (L×W) (mm) External Dimensions (L×W) (mm)																								
1005 [0402]	1.0×0.5																							
1608 [0603]	1.6×0.8																							
2012 [0805]	2.0×1.25																							
特征代号 Feature Code																								
A	For General Use																							
E	For ESD																							
H	For High Speed																							
S	For Special Request																							
<table border="1"> <tr> <th colspan="2">直流工作电压 Maximum Continuous Working Voltage</th> </tr> <tr> <th>Example</th> <th>Nominal Value</th> </tr> <tr> <td>5R5</td> <td>5.5V</td> </tr> <tr> <td>180</td> <td>18V</td> </tr> </table>	直流工作电压 Maximum Continuous Working Voltage		Example	Nominal Value	5R5	5.5V	180	18V	<table border="1"> <tr> <th colspan="2">电容 Capacitance @1MHz</th> </tr> <tr> <th>Example</th> <th>Nominal Value</th> </tr> <tr> <td>C121</td> <td>120pF</td> </tr> </table>	电容 Capacitance @1MHz		Example	Nominal Value	C121	120pF	<table border="1"> <tr> <th colspan="2">电容公差 Tolerance of Capacitance</th> </tr> <tr> <td>N</td> <td>±30%</td> </tr> <tr> <td>Y</td> <td>+100%~-50%</td> </tr> <tr> <td>G</td> <td>Maximum</td> </tr> </table>	电容公差 Tolerance of Capacitance		N	±30%	Y	+100%~-50%	G	Maximum
直流工作电压 Maximum Continuous Working Voltage																								
Example	Nominal Value																							
5R5	5.5V																							
180	18V																							
电容 Capacitance @1MHz																								
Example	Nominal Value																							
C121	120pF																							
电容公差 Tolerance of Capacitance																								
N	±30%																							
Y	+100%~-50%																							
G	Maximum																							
<table border="1"> <tr> <th colspan="2">端头代号 Terminal Code</th> </tr> <tr> <td>P</td> <td>Ni, Sn Plating</td> </tr> </table>	端头代号 Terminal Code		P	Ni, Sn Plating	<table border="1"> <tr> <th colspan="2">包装 Packing</th> </tr> <tr> <td>T</td> <td>编带 Tape & Reel</td> </tr> </table>	包装 Packing		T	编带 Tape & Reel	<table border="1"> <tr> <th colspan="2">无有害物质产品 Hazardous Substance Free Products</th> </tr> <tr> <td>F</td> <td></td> </tr> </table>	无有害物质产品 Hazardous Substance Free Products		F											
端头代号 Terminal Code																								
P	Ni, Sn Plating																							
包装 Packing																								
T	编带 Tape & Reel																							
无有害物质产品 Hazardous Substance Free Products																								
F																								

外观尺寸

Shape and Dimensions



Unit: mm [inch]

Type	L	W	T	a
SDV1005 [0402]	1.0±0.15 [.039±.006]	0.5±0.15 [.020±.006]	0.5±0.15 [.020±.006]	0.25±0.1 [.010±.004]
SDV1608 [0603]	1.6±0.15 [.063±.006]	0.8±0.15 [.031±.006]	0.8±0.15 [.031±.006]	0.3±0.2 [.012±.008]
SDV2012 [0805]	2.0±0.2 [.079±.008]	1.25±0.2 [.049±.008]	0.85±0.2 [.033±.008]	0.5±0.3 [.020±.012]

规格特性
Specifications

SDV1608A TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	测试条件 Test Condition	<20μA		8/20μs	ESD	Energy 10/1000μs	Peak Current 8/20μs	
单位 Units	DC	AC RMS	@1mA DC					Volts
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV1608A090C121 □ PTF	9.0	6.4	11.0-16.0	20	26	0.05	20	120
SDV1608A090C141 □ PTF	9.0	6.4	11.0-16.0	20	26	0.05	20	140
SDV1608A090C201 □ PTF	9.0	6.4	11.0-16.0	20	26	0.1	30	200
SDV1608A090C231 □ PTF	9.0	6.4	11.0-16.0	20	26	0.1	30	230
SDV1608A090C361 □ PTF	9.0	6.4	11.0-16.0	20	26	0.1	30	360
SDV1608A140C121 □ PTF	14.0	10.0	16.0-22.0	30	39	0.05	20	120
SDV1608A140C141 □ PTF	14.0	10.0	16.0-22.0	30	39	0.05	20	140
SDV1608A140C251 □ PTF	14.0	10.0	16.0-22.0	30	39	0.1	30	250
SDV1608A140C361 □ PTF	14.0	10.0	16.0-22.0	30	39	0.1	30	360
SDV1608A180C121 □ PTF	18.0	12.7	22.0-28.0	40	48	0.05	20	120
SDV1608A180C141 □ PTF	18.0	12.7	22.0-28.0	40	48	0.05	20	140
SDV1608A180C231 □ PTF	18.0	12.7	22.0-28.0	40	48	0.1	30	230
SDV1608A180C361 □ PTF	18.0	12.7	22.0-28.0	40	48	0.1	30	360
SDV1608A220C121 □ PTF	22.0	15.6	26.0-34.0	45	54	0.05	20	120
SDV1608A220C141 □ PTF	22.0	15.6	26.0-34.0	45	54	0.05	20	140
SDV1608A220C161 □ PTF	22.0	15.6	26.0-34.0	45	54	0.1	30	160
SDV1608A220C231 □ PTF	22.0	15.6	26.0-34.0	45	54	0.1	30	230
SDV1608A260C121 □ PTF	26.0	18.4	31.0-38.0	58	70	0.1	30	120
SDV1608A260C161 □ PTF	26.0	18.4	31.0-38.0	58	70	0.1	30	160
SDV1608A300C121 □ PTF	30.0	21.3	37.0-46.0	65	78	0.1	30	120
SDV1608A300C141 □ PTF	30.0	21.3	37.0-46.0	65	78	0.1	30	140

SDV2012A TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage	额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	测试条件 Test Condition	<20μA			8/20μs	Energy 10/1000μs	
单位 Units	DC	AC RMS	@1mA DC	Volts			Joules
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C ⁻¹	E _T	I _P	C
SDV2012A090C701 □ PTF	9.0	6.4	11.0-16.0	20	0.2	60	700
SDV2012A090C102 □ PTF	9.0	6.4	11.0-16.0	20	0.3	120	1000
SDV2012A140C401 □ PTF	14.0	10.0	16.0-22.0	30	0.2	60	400
SDV2012A140C701 □ PTF	14.0	10.0	16.0-22.0	30	0.3	120	700
SDV2012A140C901 □ PTF	14.0	10.0	16.0-22.0	30	0.4	150	900
SDV2012A180C301 □ PTF	18.0	12.7	22.0-28.0	40	0.2	60	300
SDV2012A180C501 □ PTF	18.0	12.7	22.0-28.0	40	0.3	120	500
SDV2012A180C701 □ PTF	18.0	12.7	22.0-28.0	40	0.4	150	700
SDV2012A220C251 □ PTF	22.0	15.6	26.0-34.0	45	0.2	60	250
SDV2012A220C401 □ PTF	22.0	15.6	26.0-34.0	45	0.3	120	400
SDV2012A220C501 □ PTF	22.0	15.6	26.0-34.0	45	0.3	120	500
SDV2012A260C251 □ PTF	26.0	18.4	31.0-38.0	58	0.2	60	250
SDV2012A260C401 □ PTF	26.0	18.4	31.0-38.0	58	0.3	120	400
SDV2012A300C181 □ PTF	30.0	21.3	37.0-46.0	65	0.2	60	180
SDV2012A300C301 □ PTF	30.0	21.3	37.0-46.0	65	0.3	120	300



规格特性
Specifications

SDV1005E TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					@0.5Vrms, 1MHz
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV1005E090C180 □ PTF	9.0	6.4	11.0-16.0	20	26	0.005	3	18
SDV1005E090C300 □ PTF	9.0	6.4	11.0-16.0	20	26	0.005	5	30
SDV1005E090C500 □ PTF	9.0	6.4	11.0-16.0	20	26	0.01	10	50
SDV1005E090C800 □ PTF	9.0	6.4	11.0-16.0	20	26	0.02	15	80
SDV1005E140C180 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	3	18
SDV1005E140C300 □ PTF	14.0	10.0	16.0-22.0	30	39	0.01	5	30
SDV1005E140C500 □ PTF	14.0	10.0	16.0-22.0	30	39	0.02	10	50
SDV1005E140C800 □ PTF	14.0	10.0	16.0-22.0	30	39	0.03	15	80
SDV1005E180C150 □ PTF	18.0	12.7	22.0-28.0	40	48	0.005	2	15
SDV1005E180C180 □ PTF	18.0	12.7	22.0-28.0	40	48	0.01	5	18
SDV1005E180C300 □ PTF	18.0	12.7	22.0-28.0	40	48	0.02	10	30
SDV1005E180C500 □ PTF	18.0	12.7	22.0-28.0	40	48	0.02	10	50
SDV1005E220C150 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	2	15
SDV1005E220C180 □ PTF	22.0	15.6	26.0-34.0	45	54	0.01	5	18
SDV1005E220C300 □ PTF	22.0	15.6	26.0-34.0	45	54	0.02	10	30
SDV1005E220C500 □ PTF	22.0	15.6	26.0-34.0	45	54	0.02	10	50

SDV1608E TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					@0.5Vrms, 1MHz
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV1608E090C180 □ PTF	9.0	6.4	11.0-16.0	20	26	0.005	3	18
SDV1608E090C300 □ PTF	9.0	6.4	11.0-16.0	20	26	0.005	5	30
SDV1608E090C500 □ PTF	9.0	6.4	11.0-16.0	20	26	0.01	10	50
SDV1608E090C800 □ PTF	9.0	6.4	11.0-16.0	20	26	0.02	15	80
SDV1608E090C101 □ PTF	9.0	6.4	11.0-16.0	20	26	0.05	20	100
SDV1608E140C180 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	3	18
SDV1608E140C300 □ PTF	14.0	10.0	16.0-22.0	30	39	0.01	5	30
SDV1608E140C500 □ PTF	14.0	10.0	16.0-22.0	30	39	0.02	10	50
SDV1608E140C800 □ PTF	14.0	10.0	16.0-22.0	30	39	0.03	15	80
SDV1608E140C101 □ PTF	14.0	10.0	16.0-22.0	30	39	0.05	20	100
SDV1608E180C180 □ PTF	18.0	12.7	22.0-28.0	40	48	0.005	5	18
SDV1608E180C300 □ PTF	18.0	12.7	22.0-28.0	40	48	0.02	10	30
SDV1608E180C600 □ PTF	18.0	12.7	22.0-28.0	40	48	0.02	10	60
SDV1608E180C800 □ PTF	18.0	12.7	22.0-28.0	40	48	0.03	15	80
SDV1608E180C101 □ PTF	18.0	12.7	22.0-28.0	40	48	0.05	20	100
SDV1608E220C180 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	5	18
SDV1608E220C300 □ PTF	22.0	15.6	26.0-34.0	45	54	0.02	10	30
SDV1608E220C500 □ PTF	22.0	15.6	26.0-34.0	45	54	0.02	10	50
SDV1608E220C800 □ PTF	22.0	15.6	26.0-34.0	45	54	0.03	15	80
SDV1608E220C101 □ PTF	22.0	15.6	26.0-34.0	45	54	0.05	20	100
SDV1608E260C180 □ PTF	26.0	18.4	31.0-38.0	58	70	0.02	5	18
SDV1608E260C300 □ PTF	26.0	18.4	31.0-38.0	58	70	0.03	10	30
SDV1608E260C500 □ PTF	26.0	18.4	31.0-38.0	58	70	0.03	10	50

规格特性
Specifications

SDV2012E TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					@0.5Vrms, 1MHz
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV2012E180C101 □ PTF	18.0	12.7	22.0-28.0	40	48	0.05	20	100
SDV2012E260C800 □ PTF	26.0	18.4	31.0-38.0	58	70	0.05	20	80
SDV2012E220C101 □ PTF	22.0	15.6	26.0-34.0	45	54	0.05	20	100
SDV2012E300C500 □ PTF	30.0	21.3	37.0-46.0	65	78	0.05	15	50

SDV1005H TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					@0.5Vrms, 1MHz
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV1005H140C100 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	2	10
SDV1005H140C120 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	2	12
SDV1005H180C050YPTF	18.0	12.7	22.0-28.0	40	48	0.005	2	5
SDV1005H180C100 □ PTF	18.0	12.7	22.0-28.0	40	48	0.005	2	10
SDV1005H220C030YPTF	22.0	15.6	26.0-34.0	45	54	0.003	1	3
SDV1005H220C050YPTF	22.0	15.6	26.0-34.0	45	54	0.005	2	5
SDV1005H220C100 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	2	10
SDV1005H220C120 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	2	12
SDV1005H260C030YPTF	26.0	18.4	31.0-38.0	58	70	0.003	1	3
SDV1005H260C100 □ PTF	26.0	18.4	31.0-38.0	58	70	0.005	2	10
SDV1005H260C120 □ PTF	26.0	18.4	31.0-38.0	58	70	0.005	2	12

SDV1608H TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					@0.5Vrms, 1MHz
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C ⁻¹	V _C ⁻²	E _T	I _P	C
SDV1608H140C100 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	2	10
SDV1608H140C120 □ PTF	14.0	10.0	16.0-22.0	30	39	0.005	2	12
SDV1608H180C050YPTF	18.0	12.7	22.0-28.0	40	48	0.003	1	5
SDV1608H180C100 □ PTF	18.0	12.7	22.0-28.0	40	48	0.005	2	10
SDV1608H180C120 □ PTF	18.0	12.7	22.0-28.0	40	48	0.005	2	12
SDV1608H220C030YPTF	22.0	15.6	26.0-34.0	45	54	0.003	1	3
SDV1608H220C050YPTF	22.0	15.6	26.0-34.0	45	54	0.003	1	5
SDV1608H220C100 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	2	10
SDV1608H220C120 □ PTF	22.0	15.6	26.0-34.0	45	54	0.005	2	12
SDV1608H260C030YPTF	26.0	18.4	31.0-38.0	58	70	0.003	1	3
SDV1608H260C100 □ PTF	26.0	18.4	31.0-38.0	58	70	0.005	2	10
SDV1608H260C120 □ PTF	26.0	18.4	31.0-38.0	58	70	0.005	2	12
SDV1608H300C100 □ PTF	30.0	21.3	37.0-46.0	65	78	0.005	2	10

规格特性
Specifications

SDV1005S TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C ^{*1}	V _C ^{*2}	E _T	I _P	C
SDV1005S5R5C030YPTF	5.5	4.0	31.0-38.0	58	70	0.003	1	3
SDV1005S5R5C050YPTF	5.5	4.0	22.0-28.0	40	48	0.003	1	5
SDV1005S5R5C100 □ PTF	5.5	4.0	22.0-28.0	40	48	0.005	2	10
SDV1005S5R5C120 □ PTF	5.5	4.0	22.0-28.0	40	48	0.005	2	12
SDV1005S090C030YPTF	9.0	6.4	31.0-38.0	58	70	0.003	1	3
SDV1005S090C050YPTF	9.0	6.4	22.0-28.0	40	48	0.003	1	5
SDV1005S090C100 □ PTF	9.0	6.4	22.0-28.0	40	48	0.005	2	10
SDV1005S090C120 □ PTF	9.0	6.4	22.0-28.0	40	48	0.005	2	12
SDV1005S140C030YPTF	14.0	10.0	31.0-38.0	58	70	0.003	1	3
SDV1005S140C050YPTF	14.0	10.0	22.0-28.0	40	48	0.003	1	5
SDV1005S180C030YPTF	18.0	12.7	31.0-38.0	58	70	0.003	1	3
SDV1005S360C050YPTF	36.0	25.4	46.0-60.0	130	155	0.003	1	5
SDV1005S420C050YPTF	42.0	29.7	51.0-81.0	135	160	0.005	2	5

SDV1608S TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		电容 Typical Capacitance
	DC	AC RMS		8/20 μ s	ESD	Energy 10/1000 μ s	Peak Current 8/20 μ s	
测试条件 Test Condition	<20 μ A		@1mA DC					
单位 Units	Volts	Volts	Volts	Volts	Volts	Joules	Amps	pF
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C ^{*1}	V _C ^{*2}	E _T	I _P	C
SDV1608S5R5C030YPTF	5.5	4.0	31.0-38.0	58	70	0.003	1	3
SDV1608S5R5C050YPTF	5.5	4.0	22.0-28.0	40	48	0.003	1	5
SDV1608S5R5C100 □ PTF	5.5	4.0	22.0-28.0	40	48	0.005	2	10
SDV1608S5R5C120 □ PTF	5.5	4.0	22.0-28.0	40	48	0.005	2	12
SDV1608S090C030YPTF	9.0	6.4	31.0-38.0	58	70	0.003	1	3
SDV1608S090C050YPTF	9.0	6.4	22.0-28.0	40	48	0.003	1	5
SDV1608S090C100 □ PTF	9.0	6.4	22.0-28.0	40	48	0.005	2	10
SDV1608S090C120 □ PTF	9.0	6.4	22.0-28.0	40	48	0.005	2	12
SDV1608S140C030YPTF	14.0	10.0	31.0-38.0	58	70	0.003	1	3
SDV1608S140C050YPTF	14.0	10.0	22.0-28.0	40	48	0.003	1	5
SDV1608S180C030YPTF	18.0	12.7	31.0-38.0	58	70	0.003	1	3

※VDC：压敏电阻的最大直流工作电压必须大于或等于应用电路电压的 1.5 倍 VDC ≥ 1.5 Vn>。
※V_{DC}：Max DC working voltage of varistor must exceed or equal to 1.5 times that of the application circuit voltage, V_{DC} ≥ 1.5 Vn.

※□：请明确电容公差代码 (N=±30%, Y=+100%~-50%, G=Maximum).
※□：Please specify the capacitance tolerance code (N=±30%, Y=+100%~-50%, G=Maximum).

※*1：V_C，在指定脉冲电流和波形下测量的压敏电阻两端的最大峰值电压。

能量等级	脉冲和波形
0.00-0.05 Joule	1A, 8/20 μ s
0.10 Joule	2A, 8/20 μ s
0.20-0.50 Joule	5A, 8/20 μ s

※*1：V_C，Maximum peak voltage across the varistor measured at a specified pulse current and waveform.

Energy Rating	Pulse & Waveform
0.00-0.05 Joule	1A, 8/20 μ s
0.10 Joule	2A, 8/20 μ s
0.20-0.50 Joule	5A, 8/20 μ s

※*2：V_C，压敏电阻的最大峰值电压，按照IEC61000-4-2 30A/8kV加上脉冲后30ns测量到。

※*2：V_C，Maximum peak voltage across the varistor measured at 30ns after initiation of pulse on IEC61000-4-2 30A/8kV.

可根据客户需求提供其他电气特性产品，请联系您当地的销售人员。
And products with other electrical characteristics can be provided upon customer's request. Please contact your local sales.

规格特性
Specifications

Ultra low capacitance type (C=0.5pF, 1pF or 2pF)

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	电容 Typical Capacitance	截止频率 Min. Cut-off Frequency
测试条件 Test Condition	<20μA		@1mA DC	@0.5Vrms, 1MHz	@-3dB
	DC.5	AC RMS			
Units 单位	Volts	Volts	Volts	pF	MHz
Symbol 符号	V _{WDC}	V _{WAC}	V _B	C	f ₀
SDV1005S5R5C0R5YPTF	5.5	4.0	100-160	0.5	2000
SDV1005S5R5C010YPTF	5.5	4.0	100-160	1	1250
SDV1005S5R5C020YPTF	5.5	4.0	60-80	2	600
SDV1005S090C0R5YPTF	9.0	6.4	100-160	0.5	2000
SDV1005S090C010YPTF	9.0	6.4	100-160	1	1250
SDV1005S090C020YPTF	9.0	6.4	60-80	2	600
SDV1005S140C0R5YPTF	14.0	10.0	100-160	0.5	2000
SDV1005S140C010YPTF	14.0	10.0	100-160	1	1250
SDV1005S140C020YPTF	14.0	10.0	60-80	2	600
SDV1005S180C0R5YPTF	18.0	12.7	100-160	0.5	2000
SDV1005S180C010YPTF	18.0	12.7	100-160	1	1250
SDV1005S180C020YPTF	18.0	12.7	60-80	2	600
SDV1005H260C0R5YPTF	26.0	18.4	100-160	0.5	2000
SDV1005H260C010YPTF	26.0	18.4	100-160	1	1250
SDV1005H260C020YPTF	26.0	18.4	60-80	2	600

Ultra low capacitance type (C=0.5pF, 1pF or 2pF)

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	电容 Typical Capacitance	截止频率 Min. Cut-off Frequency
测试条件 Test Condition	<20μA		@1mA DC	@0.5Vrms, 1MHz	@-3dB
	DC	AC RMS			
单位 Units	Volts	Volts	Volts	pF	MHz
符号 Symbol	V _{WDC}	V _{WAC}	V _B	C	f ₀
SDV1608S5R5C0R5YPTF	5.5	4.0	100-160	0.5	2000
SDV1608S5R5C010YPTF	5.5	4.0	100-160	1	1250
SDV1608S5R5C020YPTF	5.5	4.0	60-80	2	600
SDV1608S090C0R5YPTF	9.0	6.4	100-160	0.5	2000
SDV1608S090C010YPTF	9.0	6.4	100-160	1	1250
SDV1608S090C020YPTF	9.0	6.4	60-80	2	600
SDV1608S140C0R5YPTF	14.0	10.0	100-160	0.5	2000
SDV1608S140C010YPTF	14.0	10.0	100-160	1	1250
SDV1608S140C020YPTF	14.0	10.0	60-80	2	600
SDV1608S180C0R5YPTF	18.0	12.7	100-160	0.5	2000
SDV1608S180C010YPTF	18.0	12.7	100-160	1	1250
SDV1608S180C020YPTF	18.0	12.7	60-80	2	600
SDV1608H260C0R5YPTF	26.0	18.4	100-160	0.5	2000
SDV1608H260C010YPTF	26.0	18.4	100-160	1	1250
SDV1608H260C020YPTF	26.0	18.4	60-80	2	600

※VDC：压敏电阻的最大直流工作电压必须大于或等于应用电路电压的1.5倍 VDC ≥ 1.5 Vn。

※V_{DC}：Max DC working voltage of varistor must exceed or equal to 1.5 times that of the application circuit voltage, V_{DC} ≥ 1.5 Vn.

※：可根据客户需求提供其他电气特性产品。请联系您当地的销售人员。

※：Products with other electrical characteristics can be provided upon customer's request. Please contact your local sales.