


- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperatuer Range: -40℃~ +105℃
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000mΩ Min
 - 6、Withstanding Voltang: 800V AC/minute
 - 7、Material: Phosphoric bronze Tin-plated
 - 8、Applicable Wire Sizes:AWG#22-28#
- Qty/Reel: 12000 PCS

TYPE	Dimension mm				适用线规 AWG#	Qty/Reel
	A1	B1	A2	B2		
HC-PHB-T-A-05(低脚)	2.0	1.8	1.5	1.5	28-24	12000 PCS
HC-PHB-T-05	2.1	2.3	1.6	1.7	24-22	12000 PCS



初版发行		变更内容 MODIFY CONTENT		日期 MODIFY DATE		GENERAL TOLERANCE		制图 DRAWING		05		 深圳市华灿天禄电子有限公司 ShenzhenuacantianluELECTRONICS CO.,LTD							
变更内容 MODIFY CONTENT		日期 MODIFY DATE		GENERAL TOLERANCE		制图 DRAWING		05											
初版发行		变更内容 MODIFY CONTENT		日期 MODIFY DATE		GENERAL TOLERANCE		制图 DRAWING		05		产品名称 TITLE		PHB (2.0) 端子		版本 REV.		A	
变更内容 MODIFY CONTENT		日期 MODIFY DATE		GENERAL TOLERANCE		制图 DRAWING		05		05		产品料号 PART NO.		HC-PHB-T		单位 UNITS		mm	
变更内容 MODIFY CONTENT		日期 MODIFY DATE		GENERAL TOLERANCE		制图 DRAWING		05		05		材料 MATERIAL				页次 SHEET		1/1	